



# TVX-RoIP3

The **TVX-RoIP3** is a Radio Over IP Gateway, offering an excellent performance and cost effective standalone solution.

It is designed to interconnect Push to Talk over cellular network users with LMR radio users or connect a diverse range of two-way radio systems across channels or sites.

The **TVX-RoIP3** is equipped with a 3rd generation super dynamic Intelligent Audio Tracking System (iDATSIII), Android Operating System and our TeamVOX PTT app to offer you fast and stable Push-to-Talk communication anytime anywhere in the world.



## Conectivity

Ethernet	10/100 Base-T
Bluetooth	BT 4.0 LE
USB	Micro

## Hardware

Processor	MT6737 QuadCore ARM-A53 @ 1.1-1.3GHz
Memory	RAM 1G ROM 8G
SD Card	Micro SD
Display	LCD 4.3" Capacitive Touch
Resolution	240x320 pixels
Power Source	DC 5V
Current consumption	600mA (Typical)
Control Keys	Menu and Back
Carrier activation detection	Lower than 0.5 seg
Interconnect digital stabilizer	Enabled or disabled switch
AC Adapter	AC 100-240V Input, DC 5V 2A Output

## Software

Operating System	Android™ 7.0
Pre-installed app	TeamVOX PTT



## Physical and Durability Specs

Dimensions	160mmx100mmx40 mm (L x W x H)
Weight	450 g
IP Rating	IP54



This device has been optimized to run the following application:  
TeamVOX PTT

All rights reserved 2021.

All images are illustrative. Contact your Authorized Distributor for more information. Technical Information may change without prior notice

**Authorized Distributor:**

